


## FieldLink® DeviceNet



### Design

#### a) Pair 02YS(ST) 1X2X1.3/3.8-120 LI VZN

Wire

Stranded tinned copper wire 19 X 0.25  
Insulation of foamed Polyethylene (PE) with skin  
Wall thickness about 1.2 mm

∅ 1.3 mm (0.051 in)  
∅ 3.8 mm (0.150 in)

2 wires, WH and BU side by side  
Alulaminat foil overlapped, applied longitudinally

#### b) Pair LIY(ST) 1X2X1.5/2.7 VZN

Wire

Stranded tinned copper wire 19 X 0.34  
Insulation of Polyvinylchloride (PVC)  
Wall thickness about 0.5 mm

∅ 1.7 mm (0.067 in)  
∅ 2.7 mm (0.106 in)

2 wires, RD and BK side by side  
Alulaminat foil overlapped, applied longitudinally

### Core:

Central element: Stranded tinned copper drain wire 0.86 mm<sup>2</sup> (19x0.24)

1 Pair 02YS(ST) 1X2X1.3/3.8-120 LI VZN

1 Pair LIY(ST) 1X2X1.5/2.7 VZN

+ fillers

Shield braiding of tinned copper wires 0.13 mm dia

Coverage about 70%

∅ 8.4 mm (0.331 in)

## LEONI Special Cables GmbH

Technisches Datenblatt – Technical Data Sheet – Technisches Datenblatt – Technical Data Sheet – Technisches Datenblatt – Technical Data Sheet

### Jacket:

Polyvinylchloride (PVC) GY

Wall thickness about 1.3 mm

ø (11.0 ±0.5) mm (0.433 ±0.020 in)

Printing: LEONI L DeviceNet Thick Cable 2x18AWG 2x15AWG SHIELDED (UL) E119100

CMG 75 °C or PLTC FT4 Sun Res

Textintervals about 300 mm

### Electrical data at 20°C

Conductor resistance	(Pair to a)	≤	22.6	Ohm/km
Conductor resistance	(Pair to b)	≤	11.7	Ohm/km
Capacitance (1 kHz wire/wire)	(Pair to a)	≈	39.8	nF/km
Characteristic impedance (1 MHz)	(Pair to a)		(120 ±12)	Ohm
Signal run time	(Pair to a)	≤	4.46	ns/m
Capacity unbalanced to ground	(Pair to a)	≤	3937	pF/km
Operating voltage (peak)		≤	300	V
Insulation resistance		≥	20	MOhm*km
Test voltage (wire/wire/screen rms 50Hz 1min)		=	2000	V

Frequency (kHz)	125	500	1000
Attenuation typ. (dB/100m) (Pair to a) (dB/100ft)	0,42 (0,1)	0,81 (0,2)	1,31 (0,4)

### Mechanical and thermal characteristics

Conductor/Screen material acc. to DIN EN 13602 Cu-ETP-A...-B

Insulating material acc. to DIN EN 50290-2-23 (VDE 0819), table 2/A (HD 624.3)

Insulating material acc. to DIN EN 50290-2-21 (VDE 0819), compoundtype TI53 (HD 624.1)

Jacket material acc. to DIN VDE 0207, compoundtype YM3

Sunlight resistant acc. to UL 1581 Sec.1200

Flame retardant acc. to UL 1685 (CSA FT 4)

UL File E119100 Vol.1 Sec.17 Page 3

UL File E116441 Vol.1 Sec.7 Page 3

### Other characteristics:

Permissible temperature range : -20°C (-4°F) up to +80°C (+176°F)

Min. bending radius allowed : repeated 10X ø, single 5X ø

PVC weight with Phthalate : 54 Kg/km (36,2 lb/1000ft)

PVC weight without Phthalate : 9 Kg/km (6,0 lb/1000ft)

Weight about : 162 Kg/km (108,6 lb/1000ft)

### Designation of order of order:

L45467-F21-W55

207039

02YS 1X2X1.3/3.8-120 LI VZN PIMF

LIY CY 1X2X1.5 VZN PIMF GR

1000 m (3281 ft) on non-returnable reel