

# FieldLink®

## Industrial Ethernet Cat 5e ES



### Design

#### Wire:

Bare copper wire ø 0.64 mm  
 Insulation of Polyethylene (PE) ø 1.5 mm

#### Core:

Filler as central element  
 1. layer: 4 wires twisted  
 Sequence of colors: WH-YE-BU-OG  
 Plastic tape, overlapped  
 Inner jacket: Polyvinylchloride (PVC) ø 3.9 mm  
 Alulaminat foil overlapped, applied longitudinally  
 Shield braiding of tinned copper wires 0.13 mm dia  
 Coverage about 90% ø 4.5 mm

#### Jacket:

Polyvinylchloride (PVC) GN  
 Wall thickness about 0.9 mm ø (6.5 ±0.2) mm

Printing: LEONI L INDUSTRIAL ETHERNET STANDARD CABLE \* PROFINET Type A ES CAT5 PLUS \* 2x2x22AWG (SHIELDED) (UL) E119100 CMG 75°C VERIFIED (UL) CAT 5E or PLTC or AWM 21694 600V FT4 SUN RES \* "year/internal order number" "sequential length in metres"

### Electrical data at 20°C

Loop resistance	≤	115	Ohm/km
Signal run time	≤	5.3	ns/m
Insulation resistance	≥	500	MOhm*km
Characteristic impedance 1 – 100 MHz		(100 ±15)	Ohm
Surface transfer impedance 10 MHz	≤	10	mOhm/m
Test voltage (wire/wire/screen rms 50Hz 1min)		2000	V

**Near-end crosstalk attenuation**

Frequency (MHz)	1	4	10	16	20	31.25	62.5	100
typ. value (dB - 100m)	80	75	70	65	63	60	55	50

**Attenuation**

Frequency (MHz)	1	4	10	16	20	31.25	62.5	100
typ. value (dB/100m) (dB/100ft)	1,6 (0,5)	3,2 (1,0)	5,2 (1,6)	6,9 (2,1)	7,8 (2,4)	10,5 (3,2)	15 (4,6)	19,5 (5,9)

The electrical requirements acc. to EN 50288-2-1

**Mechanical and thermal characteristics**

Conductor material acc. to DIN EN 13602 Cu-ETP-A...

Screen material acc. to DIN EN 13602 Cu-ETP-A...-B

Insulating material acc. to DIN EN 50290-2-23 (VDE 0819), table L/MD (HD 624.3)

Jacket material acc. to DIN EN 50290-2-22 (VDE 0819), compoundtype TM52 (HD 624.2)

Flame retardant acc. to IEC 60332-1-2

Flame retardant acc. to UL 1685 (CSA FT 4)

UL-File E119100 Vol.1 Sec.12 Page 1

UL-File E352715 Vol.1 Sec. 1 Page 2 Verified CAT 5E

UL-File E116441 Vol.1 Sec. 6 Page 8

UL-File E306668 Vol.1 Sec. 3 Page 1

UL-Style 21694

**Other characteristics:**

Sunlight resistant acc. to UL 1581 Sec.1200

Limited oil resistance

Tensile loading:  $\leq 150$  N

Permissible temperature range : - 40°C up to +75°C

During laying : - 20°C up to +60°C

Transport temperature range : - 40°C up to +75°C

Min. bending radius allowed : repeated 7,5X  $\emptyset$ , single 3X  $\emptyset$

PVC weight with Phthalate : 30.4 Kg/km

PVC weight without Phthalate : 0.0 Kg/km

Weight about : 66 Kg/km (45 lb/1000ft)

**Application:**

Cable for permanent installation

**Designation of order:**

L45467-J16-B35

202284

2YY(ST)CY 2X2X0.64/1.5-100 GN

2000 m (6562 ft) on non-returnable reel